


PARAPROJECT®

Case i10 Typ-C

Protect , Charge , Sync , Transport , Flex2Connect



Part denomination	PARAPROJECT Case i10 Typ-C Charge & Sync, incl. USB-C® cable, black
Part number	208642151
GTIN /EAN	4006793003415
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1, DIN EN 55022, DIN EN 55035
Scope of delivery	- PARAPROJECT® Case i10 - device connection cable, EU, length: 5 m - USB connection cable, length: 3 m - 10 data and charging cable USB-A to USB-C® - y-adapter, C14 plug with 1 IBM sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1) - y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2) - user guide
Materials	- X-ABS plastic - industrial leather - Con-Pearl® - aluminium
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø 75 mm (with 2 lockable castors)
External dimensions (WxDxH)	530 mm x 390 mm x 540 mm
Weight	12000 g
Transport dimensions	560 mm x 410 mm x 550 mm
Dimensions of euro-palettts	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	12
customs tariff number	85044083
Country of origin	RO

PARAPROJECT®

Case i10 Typ-C

Protect , Charge , Sync , Transport , Flex2Connect

Fittings	- Interior technical equipment: - 10 storage compartments (W x D x H: 29 x 210 x 310 mm) for iPad/tablets - storage compartments (W x D x H: 28 x 235 x 260 mm) for master laptop - storage compartment for accessories such as access point, router and/or Apple TV - sync and charging unit - 10 data and charging cable USB-A to USB-C® - internal timer to set charge time limit - temperature sensor - 2 sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Compatible devices	All tablets that can be charged by USB-C®
Max. number of devices	10
Operating system	iOS / Windows / Android
Cable types for equipment	data and charging cable USB-A to USB-C® ; y-adapter, C14 plug with 1 IBM sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1) ; y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)
Power supply	central power supply for all devices
Output power per port	2,4A
Optional accessories	- data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable with LED display USB-A to Lightning® - data and charging cable USB-A to Lightning®
Lock types	combination lock
Connections	- outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - 10 USB-A ports for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 x IBM-Buchse (C5, 3-polig) und 1 x Euro-8-Buchse (C7, 2-polig, AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 x Euroflat-Buchse (2-polig) und 1 x Euro-8-Buchse (C7, 2-polig, AUX 2)
Data of currents	- 100-240V, max. 3,6A, 50/60Hz
Dimension of pockets	29 x 210 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Dimensions of other pockets	28 x 235 x 320 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case i10 Typ-C

Protect , Charge , Sync , Transport , Flex2Connect



- LED charging indicator



- sync and network connector