

PARAPROJECT®

Case CC16 CargoCase

Protect , TwinCharge , Transport



Part denomination	PARAPROJECT Case CC16 CargoCase USB-C®, without cable, black
Part number	643301039916
GTIN /EAN	4006793003385
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	<ul style="list-style-type: none">- PARAPROJECT® Case CC16 CargoCase, with integrated TwinCharge modules technology- device connection cable, EU, length: 5 m- 4 TwinCharge modules with USB-A and USB-C® ports- 2 keys- user guide
Materials	<ul style="list-style-type: none">- polypropylene- Con-Pearl®
Transport	4-fold telescopic handle / 3 carrying handles / 2 smooth-running castors ø 80 mm
External dimensions (WxDxH)	600 mm x 400 mm x 340 mm
Weight	10000 g
Transport dimensions	605 mm x 405 mm x 345 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1740 mm
Number of euro-pallet	12
customs tariff number	42021250
Country of origin	RO

PARAPROJECT®

Case CC16 CargoCase

Protect , TwinCharge , Transport

Fittings	<ul style="list-style-type: none"> - Interior technical equipment: - 16 storage compartments (W x D x H: 22 x 200 x 270 mm) for iPad/tablets - storage compartment for accessories (W x D x H: 95 x 200 x 270 mm) - 4 TwinCharge modules modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards - 20 x USB-A and USB-C® ports each - temperature sensor - overvoltage protection - active fans - Case lid: - napped foam - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - main switch - telescopic handle - 3 carrying handles - draw lock - 2 smooth-running castors
Compatible devices	All tablets up to 11,5" that can be charged by USB-C® or USB-A
Max. number of devices	16
Operating system	iOS / Android / Windows
Cable types for equipment	using customer's own USB-C® or USB-A data and charging cables
Power supply	4 TwinCharge modules for the complete power supply of devices
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 16 iPad / Android tablet or Surface Go 2 tablet with 24 W each per port ; USB-C® and USB-A output (22 / 30 / 45 W): DC 5 V/9 V/12 V/15 V->3A,20 V->2.25 A
Optional accessories	<ul style="list-style-type: none"> - Data and charging cable USB-C® to USB-C® - Data and charging cable USB-C® to Lightning - Data and charging cable with LED display USB-A to Lightning® - Data and charging cable USB-A to Lightning® - Data and charging cable USB-A to USB-C®
Lock types	latch mechanism
Connections	<ul style="list-style-type: none"> - outside: - central power supply with protective cap - main switch - inside: - 20 USB-A and USB-C® ports each, optional depending on the existing charging type
Data of currents	<ul style="list-style-type: none"> - 100 - 240 V - max. 10 A - 50/60 Hz
Dimension of pockets	22 x 200 x 270 mm
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case CC16 CargoCase

Protect , TwinCharge , Transport



- main switch
- overvoltage protection



- active ventilation
- TwinCharge technology