

PARAPROJECT®

Case TC10

Protect , Charge , Transport



Part denomination	PARAPROJECT Case TC10 TwinCharge, USB-C®, without cable, black
Part number	208710151
GTIN /EAN	4006793002920
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	- PARAPROJECT® Case TC10 with integrated TwinCharge modules technology - device connection cable, EU, length: 5 m - 2 TwinCharge modules with USB-A and USB-C® ports - user guide
Materials	- X-ABS plastic - aluminium - Con-Pearl®
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø 75 mm (with 2 lockable castors)
External dimensions (WxDxH)	530 mm x 390 mm x 495 mm
Weight	10000 g
Transport dimensions	540 mm x 400 mm x 530 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1740 mm
Number of euro-pallet	12
customs tariff number	85044083
Country of origin	RO

PARAPROJECT®

Case TC10

Protect , Charge , Transport

Fittings	<ul style="list-style-type: none"> - Interior technical equipment: - 10 storage compartments (W x D x H: 28 x 255 x 310 mm) for iPad/tablets - 2 TwinCharge modules modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards - 10 USB-A and USB-C® ports each - temperature sensor - overvoltage protection - overvoltage protection - napped foam - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - main switch - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Compatible devices	All tablets up to 12,9" that can be charged by USB-C® or USB-A (QuickCharge, PD)
Max. number of devices	10
Operating system	iOS / Windows / Android
Cable types for equipment	using customer's own USB-C® or USB-A data and charging cables
Power supply	2x TwinCharge modules for the complete power supply of devices
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 10 iPad / Android tablet with 22 W each per port or 8 Surface Go 2 tablet with 24 W each per port ; USB-C® and USB-A output (22 / 30 / 45 W): DC ; 5 V / 9 V / 12 V / 15 V -> 3 A, 20 V -> 2.25 A
Optional accessories	<ul style="list-style-type: none"> - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable with LED display USB-A to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®
Lock types	combination lock
Connections	<ul style="list-style-type: none"> - outside: - central power supply with protective cap - main switch - inside: - 10 USB-A and USB-C® ports each, optional depending on the existing charging type
Data of currents	<ul style="list-style-type: none"> - 100 - 240 V - max. 5 A - 50 / 60 Hz
Dimension of pockets	28 x 255 x 295 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case TC10

Protect , Charge , Transport



- storage space for 10 hard covers
- TwinCharge technology for up to 10 slots



- temperature sensor