

# PARAPROJECT®

## Case CC20 CargoCase

Protect , Charge , Transport



Part denomination	PARAPROJECT Case CC20 CargoCase TwinCharge, without cable
Part number	6433010399
GTIN /EAN	4006793003064
Field of application	Education
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	<ul style="list-style-type: none"> <li>- PARAPROJECT® Case CC20 CargoCase, with integrated TwinCharge modules technology</li> <li>- device connection cable, EU, length: 5 m</li> <li>- 4 TwinCharge modules with USB-A and USB-C® ports</li> <li>- 2 keys</li> <li>- user guide</li> </ul>
Materials	<ul style="list-style-type: none"> <li>- polypropylene</li> <li>- Con-Pearl®</li> </ul>
Transport	telescopic handle / 3 carrying handles / 2 smooth-running castors ø 80 mm
External dimensions (WxDxH)	600 mm x 400 mm x 340 mm
Weight	10000 g
Transport dimensions	605 mm x 405 mm x 345 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1740 mm
Number of euro-pallet	16
customs tariff number	42021250
Country of origin	RO

# PARAPROJECT®

## Case CC20 CargoCase

Protect , Charge , Transport

Fittings	<ul style="list-style-type: none"> <li>- Interior technical equipment:</li> <li>- 20 storage compartments (W x D x H: 22 x 203 x 245 mm) for iPad/tablets</li> <li>- 4 TwinCharge modules modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards</li> <li>- 20 USB-A and USB-C® ports each</li> <li>- temperature sensor</li> <li>- overvoltage protection</li> <li>- active fans</li> <li>- cable protection</li> <li>- Case lid:</li> <li>- napped foam</li> <li>- air vents in the lid and rear panel</li> <li>- External technical equipment:</li> <li>- central power supply</li> <li>- main switch</li> <li>- telescopic handle</li> <li>- 3 carrying handles</li> <li>- draw lock</li> <li>- 2 smooth-running castors</li> </ul>
Compatible devices	All tablets up to 11,5" that can be charged by USB-C® or USB-A
Max. number of devices	20
Operating system	iOS / Android / Windows
Cable types for equipment	using customer's own USB-C® or USB-A data and charging cables ; USB-C® to USB-C® charging and data cables with a length of 0.3 m are recommended
Power supply	4 TwinCharge modules for the complete power supply of devices
Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 20 iPad / Android tablet with 22 W each per port, or 16 Surface Go 2 tablet with 24 W each per port ; USB-C® and USB-A output (22 / 30 / 45 W): DC 5 V/9 V/12 V/15 V->3A, 20 V->2.25 A
Optional accessories	<ul style="list-style-type: none"> <li>- Data and charging cable USB-C® to USB-C®</li> <li>- Data and charging cable USB-C® to Lightning</li> <li>- Data and charging cable with LED display USB-A to Lightning®</li> <li>- Data and charging cable USB-A to Lightning®</li> <li>- Data and charging cable USB-A to USB-C®</li> </ul>
Lock types	latch mechanism
Connections	<ul style="list-style-type: none"> <li>- outside:</li> <li>- central power supply</li> <li>- main switch</li> <li>- inside:</li> <li>- 20 USB-A and USB-C® ports each, optional depending on the existing charging type</li> </ul>
Data of currents	<ul style="list-style-type: none"> <li>- 100 - 240 V</li> <li>- max. 10 A</li> <li>- 50 / 60 Hz</li> </ul>
Dimension of pockets	22 x 203 x 245 mm
Color	anthracite

product image similar / information without content / subject to errors and changes / all dimensions in mm

# PARAPROJECT®

## Case CC20 CargoCase

Protect , Charge , Transport

