

PARAPROJECT®

Case N16

charge , transport , storage



Part denomination	PARAPROJECT Case N16 Charge Only, 12", black
Part number	208.440-15101
GTIN /EAN	4006793001268
Field of application	Education , Health Care
Certificates	CE / REACH / RoHS
Applicable standards	NRL 2011/65/EU / DIN EN 62368-1:2016-05. EMV 2014/35/EU / DIN EN 55022:210+AC:2011 / DIN EN 55035:2010. Rohs 2011/65/EU / DIN EN 50581:2012
Scope of delivery	<ul style="list-style-type: none"> - PARAPROJECT® Case N16 - device connection cable, EU, length: 5 m - network cable, length: 0.8 m - 8 y-adapter with IBM socket (C5, 3-pin) and 2 Euroflat socket (2-pin) - 8 y-adapter with Euroflat socket (2-pin) and 2 IBM socket (C5, 3-pin) - user guide - mounting hardware for access point
Materials	<ul style="list-style-type: none"> - Con-Pearl® - X-ABS plastic - aluminium - industrial leather
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø 75 mm (with 2 lockable castors)
External dimensions (WxDxH)	720 mm x 390 mm x 550 mm
Weight	16000 g
Transport dimensions	760 mm x 420 mm x 570 mm
Dimensions of euro-pallets	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	6
customs tariff number	42021250
Country of origin	RO

PARAPROJECT®

Case N16

charge , transport , storage

Fittings	<ul style="list-style-type: none"> - Interior technical equipment: - 16 storage compartments (W x D x H: 28 x 215 x 350 mm) for Tablets - storage compartment (W x D x H: 40 x 240 x 390 mm) for master laptop - storage compartment for accessories such as access point, router and/or Apple TV - 16 rubber loops for original power supply units - internal timer to set charge time limit - main switch - temperature sensor - 2 Schuko sockets for e.g. master laptop or access point - active fans - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - RJ 45 network socket for e.g. access point for e.g. access point - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Compatible devices	All tablets or laptops that can be charged with their own power supply unit
Max. number of devices	16
Operating system	Android / Chrome OS / Windows
Cable types for equipment	y-adapter with IBM socket (C5, 3-pin) and 2 Euroflat socket (2-pin) ; y-adapter with Euroflat socket (2-pin) and 2 IBM socket (C5, 3-pin)
Power supply	customer-owned power packs can be used
Output power per port	see original power supply unit
Optional accessories	<ul style="list-style-type: none"> - y-adapter with 2 EURO-8-socket (C7, 2-pin) - Y adapter with 2x EURO 8 sockets
Lock types	combination lock
Connections	<ul style="list-style-type: none"> - outside: - central power supply with protective cap - RJ 45 network socket for e.g. access point for e.g. access point - inside: - main switch - 8 IBM socket (C5, 3-pin) - 8 y-adapter with IBM socket (C5, 3-pin) and 2 Euroflat socket (2-pin) - 8 y-adapter with Euroflat socket (2-pin) and 2 IBM socket (C5, 3-pin) - 2 Schuko sockets for e.g. master laptop or access point
Data of currents	<ul style="list-style-type: none"> - 100 - 240 V - max. 3,6 A - 50/60 Hz
Dimension of pockets	28 x 215 x 300 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Dimensions of other pockets	40 x 240 x 330 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Color	black

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case N16

charge , transport , storage



- storage compartments made of Con-Pearl® material



- central power supply with protective cap