

PARAPROJECT®

Cube C₁₂

Protect, Charge, Transport





Part denomination	PARAPROJECT Cube C12 USB-C® without cable
Part number	990700999
GTIN /EAN	4006793003316
Field of application	Education
Certificates	GS / REACH / RoHS
Applicable standards	CE/EMC: EN62368.1 / IEC62368.1
Scope of delivery	- PARAPROJECT® Cube C12
22200. 20019	- device connection cable, EU, length: 2 m
	- 2 keys
	- user guide
Materials	- powder-coated steel sheet
	- ABS plastic
External dimensions (WxDxH)	500 mm x 452 mm x 390 mm
Weight	18000 g
Transport dimensions	600 mm x 490 mm x 530 mm
Dimensions of euro-plaletts	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	6
customs tariff number	94032080
Country of origin	CN
Fittings	- Interior technical equipment:
_	- 12 storage compartments (W x D x H: 32 x 380 x 290 mm) for iPad/tablets
	- 12 USB-C® ports
	- LED charging status indicator
	- temperature sensor
	- active fans
	- External technical equipment:
	- central power supply with protective cap
	- main switch
	- handle recesses on both sides
	- lockable plastic roller shutter
	- barrel lock
Commercial to the commercial t	- floor gliders
Compatible devices	all tablets / chromebooks / ultrabooks that can be charged by USB-C®
Max. number of devices	12
Operating system	iOS / Android / Windows
Cable types for equipment	using customer's own USB-C® or USB-A data and charging cables
Power supply	central power supply



PARAPROJECT®

Cube C₁₂

Protect, Charge, Transport

Output power per port	automatic adjustment via USB-PD Power Delivery and QuickCharge standards; e.g. 12 iPad / Android tablet with 45 W per port; USB-C® output; 5 V / 9 V / 10V / 12 V /15 V -> 3 A; 20 V -> 2,25 A
Optional accessories	- data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - wall holder 990624999
Lock types	barrel lock
Connections	 outside: central power supply with protective cap main switch inside: 12 USB-C® ports each
Data of currents	- 100 - 240 V - max. 8 A
Dimension of pockets	32 mm x 380 mm x 290 mm
Color	black; white

product image similar / information without content / subject to errors and changes / all dimensions in mm





- incl. LED status charging indicator
- incl. 12 x USB-C ports



- central on/off switch
- active ventilation
- central device connection and overvoltage protection