

PARAPROJECT®

Case CC20 CargoCase

Protect , Charge , Transport



| | |
|-----------------------------|---|
| Part denomination | PARAPROJECT Case CC20 CargoCase TwinCharge, USB-C®, without cable, black |
| Part number | 6433010399 |
| GTIN /EAN | 4006793003064 |
| Field of application | Education |
| Certificates | CE / REACH / RoHS |
| Applicable standards | DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035 |
| Scope of delivery | <ul style="list-style-type: none"> - PARAPROJECT® Case CC20 CargoCase, with integrated TwinCharge modules technology - device connection cable, EU, length: 5 m - 4 TwinCharge modules with USB-A and USB-C® ports - 2 keys - user guide |
| Materials | <ul style="list-style-type: none"> - polypropylene - Con-Pearl® |
| Transport | Teleskopauszug, 4-fach / 3 Tragegriffe / 2 Leichtlaufräder mit ø 80 mm |
| External dimensions (WxDxH) | 600 mm x 400 mm x 340 mm |
| Weight | 10500 g |
| Transport dimensions | 605 mm x 405 mm x 345 mm |
| Dimensions of euro-pallets | 1200 mm x 800 mm x 1740 mm |
| Number of euro-pallet | 12 |
| customs tariff number | 42021250 |
| Country of origin | RO |

PARAPROJECT®

Case CC20 CargoCase

Protect , Charge , Transport

| | |
|---------------------------|--|
| Fittings | <ul style="list-style-type: none"> - Interior technical equipment: - 20 storage compartments (W x D x H: 22 x 200 x 270 mm) for iPad/tablets - 4 TwinCharge modules modules, automatic adjustment via USB-PD Power Delivery and QuickCharge standards - 20 USB-A and USB-C® ports each - temperature sensor - overvoltage protection - active fans - Case lid: - napped foam - air vents in the lid and rear panel - External technical equipment: - central power supply - main switch - telescopic handle - 3 carrying handles - draw lock - 2 smooth-running castors |
| Compatible devices | All tablets up to 11,5" that can be charged by USB-C® or USB-A |
| Max. number of devices | 20 |
| Operating system | iOS / Android / Windows |
| Cable types for equipment | Verwendung der kundeneigenen USB-C® oder USB-A Daten- und Ladekabel |
| Power supply | 4 TwinCharge modules for the complete power supply of devices |
| Output power per port | automatic adjustment via USB-PD Power Delivery and QuickCharge standards ; e.g. 20 iPad / Android tablet with 22 W each per port, or 16 Surface Go 2 tablet with 24 W each per port ; USB-C® and USB-A output (22 / 30 / 45 W): DC 5 V/9 V/12 V/15 V->3A, 20 V->2.25 A |
| Optional accessories | <ul style="list-style-type: none"> - Data and charging cable USB-C® to USB-C® - Data and charging cable USB-C® to Lightning - Data and charging cable with LED display USB-A to Lightning® - Data and charging cable USB-A to Lightning® - Data and charging cable USB-A to USB-C® |
| Lock types | latch mechanism |
| Connections | <ul style="list-style-type: none"> - outside: - central power supply - main switch - inside: - 20 USB-A and USB-C® ports each, optional depending on the existing charging type |
| Data of currents | <ul style="list-style-type: none"> - 100 - 240 V - max. 10 A - 50 / 60 Hz |
| Dimension of pockets | 22 x 200 x 270 mm |
| Color | black |

product image similar / information without content / subject to errors and changes / all dimensions in mm

PARAPROJECT®

Case CC20 CargoCase

Protect , Charge , Transport



- active ventilation
- TwinCharge technology



- main switch
- overvoltage protection