

# PARALUX® PX1

sturdy flashlight, suitable for Zone 0, with powerful luminance



Part denomination	PARALUX® PX1
Part number	6911252158
GTIN /EAN	4006793749788
customs tariff number	85131000
Country of origin	CN
Fittings	<ul style="list-style-type: none"> <li>- flashlight ATEX and IECEx certified for Zone 0 / 21</li> <li>- 100 % watertight</li> <li>- polycarbonate with antistatic additive</li> <li>- rubberized lamp head</li> <li>- rubberized rear switch for one-hand operation</li> <li>- lamp: CREE LED XT-E (5W)</li> <li>- luminance: approx. 120 lumens</li> <li>- headlight range: approx. 150 m</li> <li>- battery type: 4x AA/Mignon/each 1.5 V</li> <li>- supplied in blister packaging including batteries</li> <li>- compatible with almost all helmet mounts and with our PARASNAP®</li> </ul>
Scope of delivery	<ul style="list-style-type: none"> <li>- 4x AA/Mignon/each 1.5 V</li> <li>- user manual</li> </ul>
Dimensions (WxDxH)	167 mm x 41 mm x 43 mm
Weight	80 g
gross weight (incl. batteries)	185 g
Protection class	<ul style="list-style-type: none"> <li>- II 1G Ex ia IIC T4 Ga</li> <li>- II 2D Ex ib IIIC T105°C Db IP68</li> </ul>
Bulb	CREE LED XT-E (5W)
Light flux	approx. 120 lumens
Light range	approx. 150 meters
Running time	approx. 15 hours full power, a total of approx. 50 hours
Material Licht	PC (polycarbonate)
Color Licht	yellow

product image similar / information without content / subject to errors and changes / all dimensions in mm