

PARAPROJECT®

Case N₁₀

charging, transport, storage





Part denomination	PARAPROJECT Case N10 Charge Only, 15.6", white
Part number	208.420-170
GTIN /EAN	4006793002302
Field of application	Education , Health Care
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	- PARAPROJECT® Case N10
	- device connection cable, EU, length: 5 m
	- 5 y-adapter with 2 x Euro-8 sockets (C7, 2-pin)
	- 5 y-adapter with 2x IBM sockets (C5, 3-pin)
	- user guide
Materials	- ABS plastic / PMMA
	- aluminium
	- Con-Pearl®
	- industrial leather
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø
	75 mm (with 2 lockable castors)
External dimensions (WxDxH)	720 mm x 390 mm x 550 mm
Weight	1400 g
Transport dimensions	760 mm x 420 mm x 570 mm
Dimensions of euro-plaletts	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	6
customs tariff number	42021250
Country of origin	RO



PARAPROJECT®

Case N₁₀

charging, transport, storage

- 10 storage compartments (W x D x H: 40 x 285 x 390 mm) for tablets or laptops - storage compartment for accessories such as access point, router and/or Apple TV - 10 rubber loops for original power supply units - internal timer to set charge time limit - main switch - Schuko sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4- smooth-running castors ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks, laptop Max. number of devices Operating system Chrome OS / Windows / Android Cable types for equipment y-adapter with 2 Euro-8 sockets (C ₇ , 2-pin); y-adapter with 2 IBM sockets (C ₅ , 3-pin) Output power per port see original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Connections Output power supply unit 2 Euroflat sockets (2-pin) - sy-adapter with 2 Euroflat sockets (2-pin) - 5 y-adapter with 2 Eurof	Fittings	- Interior technical equipment:
- storage compartment for accessories such as access point, router and/or Apple TV - 10 rubber loops for original power supply units - internal timer to set charge time limit - main switch - Schuko sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices Oberating system Chrome OS / Windows / Android Cable types for equipment Power supply use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Dottonal accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5	ŭ	
- 10 rubber loops for original power supply units - internal timer to set charge time limit - main switch - Schuko sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment - y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Output power per port See original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types - combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sock		
internal timer to set charge time limit - main switch - Schuko sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices Operating system Chrome OS / Windows / Android Cable types for equipment Output power per port Ose original power supply units Output power per port Optional accessories - y-adapter with 2 Euroflat sockets (C-, 2-pin) ; y-adapter with 2 IBM sockets (C5, 3-pin) Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Combination lock Connections Onections Onections One of Sockets (C5, 3-pin) - 5 y-adapter with 2 Euroflat sockets (C7, 2-pin) - 5 y-adapter with		
- main switch - Schuko sockets for e.g. master laptop or access point - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carnying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors) All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Output power per port see original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5		
- Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Power supply use of customer's own power supply units Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		
- Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Power supply use of customer's own power supply units Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- Schuko sockets for e.g. master laptop or access point
- air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment Power supply use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euro-8 sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5		
- air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment Power supply use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euro-8 sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5		- pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop
External technical equipment:		
- 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment Power supply use of customer's own power supply units Output power per port See original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapt		
- 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment y-adapter with 2 Euro-8 sockets (C7, 2-pin) ; y-adapter with 2 IBM sockets (C5, 3-pin) Power supply use of customer's own power supply units Output power per port Optional accessories -y-adapter with 2 Euroflat sockets (2-pin) Lock types Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) -		- central power supply with protective cap
- combination lock - 4 smooth-running castors Ø 75 mm (with 2 lockable castors) All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Power supply use of customer's own power supply units Output power per port see original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 IBM socket		- 4-fold telescopic handle
- 4 smooth-running castors ø 75 mm (with 2 lockable castors) Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit, chromebooks, laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment Y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin) Power supply Output power per port see original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Elmo-8 sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IB		- 2 carrying handles
Compatible devices All tablets or laptops up to 15,6" that can be charged with their own power supply unit , chromebooks , laptop Max. number of devices Operating system Chrome OS / Windows / Android Cable types for equipment Power supply Use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3		- combination lock
Chromebooks , laptop Max. number of devices 10 Operating system Chrome OS / Windows / Android Cable types for equipment Power supply Use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (D5, 3-pin)		- 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Max. number of devices10Operating systemChrome OS / Windows / AndroidCable types for equipmenty-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin)Power supplyuse of customer's own power supply unitsOutput power per portsee original power supply unitOptional accessories-y-adapter with 2 Euroflat sockets (2-pin)Lock typescombination lockConnections- outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access pointData of currents- 100 - 240 V - max.10 A - 50/60 HzDimension of pockets40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)Domensions of other pockets45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Compatible devices	All tablets or laptops up to 15,6" that can be charged with their own power supply unit,
Operating system Chrome OS / Windows / Android Cable types for equipment y-adapter with 2 Euro-8 sockets (C ₇ , 2-pin); y-adapter with 2 IBM sockets (C ₅ , 3-pin) Power supply use of customer's own power supply units Output power per port see original power supply unit Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C ₅ , 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C ₇ , 2-pin) - 5 y-adapter with 2 IBM sockets (C ₅ , 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		chromebooks, laptop
Cable types for equipment Power supply use of customer's own power supply units Output power per port Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets	Max. number of devices	
Power supply Use of customer's own power supply units Output power per port See original power supply unit Optional accessories -y-adapter with 2 Euroflat sockets (2-pin) Lock types Combination lock Connections -outside: -central power supply with protective cap -inside: -main switch -5 IBM socket (C5, 3-pin) -5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) -5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents -100 - 240 V -max.10 A -50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Operating system	
Output power per port Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) Lock types combination lock Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Cable types for equipment	y-adapter with 2 Euro-8 sockets (C7, 2-pin); y-adapter with 2 IBM sockets (C5, 3-pin)
Optional accessories - y-adapter with 2 Euroflat sockets (2-pin) combination lock - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Power supply	use of customer's own power supply units
Lock types Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Output power per port	see original power supply unit
Connections - outside: - central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Optional accessories	- y-adapter with 2 Euroflat sockets (2-pin)
- central power supply with protective cap - inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 chuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Lock types	combination lock
- inside: - main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- outside:
- main switch - 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- central power supply with protective cap
- 5 IBM socket (C5, 3-pin) - 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- inside:
- 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- main switch
- 5 y-adapter with 2 IBM sockets (C5, 3-pin) - Schuko sockets for e.g. master laptop or access point Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- 5 IBM socket (C5, 3-pin)
- Schuko sockets for e.g. master laptop or access point - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- 5 y-adapter with 2 Euro-8 sockets (C7, 2-pin)
Data of currents - 100 - 240 V - max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		
- max.10 A - 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- Schuko sockets for e.g. master laptop or access point
- 50/60 Hz Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)	Data of currents	- 100 - 240 V
Dimension of pockets 40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel) Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		
Domensions of other pockets 45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)		- 50/60 Hz
	Dimension of pockets	40 x 285 x 390 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
Color white	Domensions of other pockets	45 x 220 x 260 mm (+ 50 mm zusätzliche Höhe dank Kofferdeckel)
	Color	white

 $product\ image\ similar\ /\ information\ without\ content\ /\ subject\ to\ errors\ and\ changes\ /\ all\ dimensions\ in\ mm$



PARAPROJECT®

Case N₁₀

charging, transport, storage





- 10x storage compartment for laptops up to 15.6"



 central power supply with protective cap