

# **PARAPROJECT®**

### Case i15 BASKET

charging, synchronisation, transportation, protection, Flex2Connect





Part denomination	PARAPROJECT Case i15 BASKET Charge&Sync, incl. USB Lightning® cable, black
Part number	208.650-15101
GTIN /EAN	4006793002654
Field of application	Education , Health Care
Certificates	CE / REACH / RoHS
Applicable standards	DIN EN 60950-1 / DIN EN 55022 / DIN EN 55035
Scope of delivery	- PARAPROJECT® Case i15 BASKET
	- device connection cable, EU, length: 5 m
	- USB connection cable, length: 3 m
	- 15 data and charging cable with LED display USB-A to Lightning®
	- y-adapter, C14 plug with 1 IBM sockets (C5, 3-pin) and 1 x EURO-8-socket (C7, 2-pin, AUX 1)
	- y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)
	- 3 baskets with colored, replaceable padded inserts for carrying handle (red, blue, orange and
	green)
	- user guide
	- 3 baskets with colored, replaceable padded inserts for carrying handle (red, blue, orange and
Materials	green) - X-ABS plastic
materials	- aluminium
	- industrial leather
Transport	4-fold telescopic handle / 2 carrying handles / combination lock / 4 smooth-running castors ø
	75 mm (with 2 lockable castors)
External dimensions (WxDxH)	720 mm x 390 mm x 550 mm
Weight	17000 g
Transport dimensions	760 mm x 420 mm x 570 mm
Dimensions of euro-plaletts	1200 mm x 800 mm x 1860 mm
Number of euro-pallet	6
customs tariff number	85044083
Country of origin	RO



### **PARAPROJECT®**

#### Case i15 BASKET

charging, synchronisation, transportation, protection, Flex2Connect

- storage compartment (W x D x H: 530 x 240 x 320 mm) for 3 removable baskets with 5 compartments each for IPads - storage compartments (W x D x H: 30 x 310 x 320 mm) for master laptop - storage compartment for accessories such as access point, router and/or Apple TV - sync and charging unit - 15 data and charging cable with LED display USB-A to Lightning® - temperature sensor - overvoltage protection - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - main switch - 4-fold telescopic handle - 2 carrying handles - combination lock - 4 smooth-running castors ø 75 mm (with 2 lockable castors)  All iPad from generation 4, as well as mini  Max. number of devices  All iPad from generation 4, as well as mini  Sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 IB sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)  Power supply - central power supply for all devices  Optional accessories  Optional accessories  Optional accessories  Combination lock - contral power supply with protective cap - USB-8 port for sync function - R) 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect		
Compatible devices  Max. number of devices  Operating system  iOS  Cable types for equipment  data and charging cable with LED display USB-A to Lightning®; y-adapter, C14 plug with 1 B sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)  Power supply  Central power supply for all devices  Output power per port  Optional accessories  - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Combination lock  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - R1 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  All Hand from generation 4, as well as mining year and pass of the socket (C7, 2) polig, AUX 2)  Dimension of pockets  All i Pad from generation 4, as well as mining year and pass of the socket (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 2)  Dimension of pockets  All i Pad from year and pass of the socket (C7, 2-pol AUX 2)  Dimension of pockets  All i Pad from year and the socket (C7, 2-pol AUX 2)  Dimension of pockets  All i Pad from year and the socket (C7, 2-pol AUX 2)  Dimension of pockets  All i Pad from year and the socket (C7, 2-pol AUX 2)	Fittings	compartments each for iPads - storage compartments (W x D x H: 30 x 310 x 320 mm) for master laptop - storage compartment for accessories such as access point, router and/or Apple TV - sync and charging unit - 15 data and charging cable with LED display USB-A to Lightning® - temperature sensor - overvoltage protection - Case lid: - pocket with zipper, pocket with velcro fastener and push-in compartment with rubber loop - air vents in the lid and bottom tray - External technical equipment: - central power supply with protective cap - main switch - 4-fold telescopic handle - 2 carrying handles - combination lock
Max. number of devices Operating system iOS  Cable types for equipment  data and charging cable with LED display USB-A to Lightning®; y-adapter, C14 plug with 1 IB sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 IB socket (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)  Power supply  Central power supply for all devices Output power per port  Optional accessories  - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Combination lock  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm		- 4 smooth-running castors ø 75 mm (with 2 lockable castors)
Operating system  Cable types for equipment  data and charging cable with LED display USB-A to Lightning®; y-adapter, C14 plug with 1 lB sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflation sockets (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)  Power supply  Central power supply for all devices  Output power per port  Optional accessories  - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Combination lock  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Compatible devices	All iPad from generation 4, as well as mini
data and charging cable with LED display USB-A to Lightning®; y-adapter, C14 plug with 1 lB sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2); y-adapter, C14 plug with 1 Euroflated Socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflated Socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflate	Max. number of devices	15
sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)  Power supply central power supply for all devices  Output power per port 5 V/up to 2,4 A up to 12 w  Optional accessories - data and charging cable USB-C® to USB-C® - data and charging cable USB-B to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Lock types combination lock  Connections - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Operating system	
Output power per port  Optional accessories  - data and charging cable USB-C® to USB-C® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Combination lock  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Cable types for equipment	data and charging cable with LED display USB-A to Lightning®; y-adapter, C14 plug with 1 IBM sockets (C5, 3-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 1); y-adapter, C14 plug with 1 Euroflat socket (2-pin) and 1 EURO-8-socket (C7, 2-pin, AUX 2)
Optional accessories  - data and charging cable USB-C® to USB-C® - data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Lock types  Combination lock  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Power supply	central power supply for all devices
- data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning® - data and charging cable USB-A to USB-C®  Lock types combination lock  Connections - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Output power per port	5 V/up to 2,4 A up to 12 w
Lock types  Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Optional accessories	- data and charging cable USB-C® to Lightning® - data and charging cable USB-A to Lightning®
Connections  - outside: - central power supply with protective cap - USB-B port for sync function - RJ 45 network socket for e.g. access point - optional: HDMI port - inside: - main switch - 16 USB-A for Flex2Connect - Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-pol AUX 1) - Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)  Data of currents  - 100 - 240 V - max. 3,6 A - 50/60 Hz  Dimension of pockets  (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Lock types	
- max. 3,6 A - 50/60 Hz Dimension of pockets (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Connections	<ul> <li>central power supply with protective cap</li> <li>USB-B port for sync function</li> <li>RJ 45 network socket for e.g. access point</li> <li>optional: HDMI port</li> <li>inside:</li> <li>main switch</li> <li>16 USB-A for Flex2Connect</li> <li>Y-Adapter Kabel, C14-Stecker auf 1 IBM-Buchse (C5, 3-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 1)</li> <li>Y-Adapter Kabel, C14-Stecker auf 1 Euroflach-Buchse (2-polig) und 1 Euro-8-Buchse (C7, 2-polig, AUX 2)</li> </ul>
Dimension of pockets (B x T x H) 530 x 240 x 320 mm / max. Größe 230 x 270 mm	Data of currents	- max. 3,6 A
	Dimension of pockets	-
Color black	•	


product image similar / information without content / subject to errors and changes / all dimensions in mm



# **PARAPROJECT®**

#### Case i15 BASKET

charging, synchronisation, transportation, protection, Flex2Connect





3 removable baskets for easy handling

